



H S H O L Z E X P O R T S C H U S T E R

*Gesellschaft m.b.H.*

## Technical Datasheet PELLET **CS COMBUSTICK**

<b>Length:</b>	<b>3,15 &lt; L ≤ 40 mm.</b>
<b>Diameter:</b>	<b>6 ± 1 mm.</b>
<b>Mechanical Durability:</b>	<b>≥ 98,5%</b> (as received), (at the loading point of transport unit)
<b>Net calorific value:</b>	<b>≥ 4,9</b>
<b>Moisture:</b>	<b>≤ 8%</b>
<b>Bulk Density:</b>	<b>600 ≤ BD ≤ 750 kg/m<sup>3</sup></b> (as received)
<b>Ash:</b>	<b>≤ 0,5 m-%</b> (dry basis)
<b>Packaging:</b>	<b>15 kg bags. 66 bags/pallet.</b>
<b>Certifications:</b>	<b>EN plus A1 AT 322 - DIN plus 7A134</b>
<b>Raw material:</b>	<b>Coniferous: spruce / fir</b>
<b>Origin:</b>	<b>E.U.</b>



Reg. n. 7A134



AT 322



A-6020 INNSBRUCK, MAGTSTRASSE 4A. TELEFON (0512) 22560, FAX (0512) 225607

[info@schuster-holz.at](mailto:info@schuster-holz.at), [www.schuster-holz.at](http://www.schuster-holz.at)